

TF-136

PSEUDOPLASTIC TRAINING FOAM CONCENTRATE



DESCRIPTION

Synthetic foam compound specially designed to be used for training and exhibition purposes, not for extinguishing. It allows simulate the use of the 1%, 3% or 6% conventional pseudoplastic foam concentrates, avoiding the use of expensive products. This product is formulated with synthetic surfactants easily biodegradable, with a low environmental impact. **It does not contain fluorochemicals.**

USE

Use with standard proportioning equipment and foam devices. TF-136 can be used to test, verify and exhibits foam equipment, for training fire brigades, etc, being the ideal product for training centers. It is an concentrate with extinguishing capability on class A and B (hydrocarbon) fires, but its burn-back resistance has been reduced voluntarily allowing the possibility to make successive tests in the same fire pool.



DOSAGE

The dosage rate is 1%, 3% or 6% in fresh or sea water, allowing the simulation of use of typical foam concentrates such as 1x3, 3x3, 3x6 or 6x6.

SPECIFICATIONS

At 3%, TF-136 fulfils the EN-1568-1 standard for medium expansion foams and the EN-1568-3 for low expansion foams (class IIID).

SPECIFICATIONS

CONCENTRATE	
Specific gravity @ 20°C	1.02
pH @ 20°C	7.5
Viscosity, cone and plate, mPa.s @ 20°C	74/260
Freezing point, °C	< -5°C

FOAM SOLUTION			
Dilution rate	1%	3%	6%
Surface tension at 20°C, mN/m (Demineralised water)	33	33	33
Interfacial tension with cyclohexane at 20°C, mN/m	4	4	4
Low Expansion Foam (EN 1568-3)			
Foam Expansion Index	7.0	8.2	8.4
25% Drainage Time, mins	3	9	21
Medium Expansion Foam (EN 1568-1)			
Foam Expansion Index	-	120	130
25% Drainage Time, mins	-	6:00	14:00

PACKAGING

The product is supplied in 20 or 25 L PE prismatic containers, 200 L PE cylindrical drums and 1,000 L IBC containers.

STORAGE

The foam concentrate shall be stored at temperatures between -5° and +50°C, preferably in their original containers, well closed. The product has not expiration date.

⚠ CAUTIONS

Foams should not be used in contact with electrical equipments, nor with chemical products that can react with water. It is recommended to avoid the contact of the foam concentrate with the skin. In case of eye splashes, wash with plenty of water. In case of ingestion do not induce vomit, drink water and take medical advice.



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:
www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue
Green Bay, WI 54313
Tel: +1 (920) 593-9445
salesfoamusa@perimeter-solutions.com

EMEA

Polígono Industrial de Baiña, Parcela 23
33682 Baiña-Mieres (Asturias) – Spain
Tel: +34 985 24 29 45
salesfoamea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia
Tel: +61 2 9673 5300
salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.