

SOLBERG® RE-HEALING™ RF-MB FOAM CONCENTRATE



TYPICAL PHYSICAL PROPERTIES

AT 77 °F (25 °C)

Appearance: Brown liquid

Freezing Point: 23°F (-5°C)

(No quality loss after thawing)

Maximum Storage Temp: 120°F (49°C)

pH: 7.0 - 8.5

Refractive Index: 1.3865 - 1.3869

Specific Gravity: 1.062 - 1.069

Viscosity: 3400 - 3800 cps*

Sediments: None

*Brookfield Viscometer Spindle #4,

Speed 30 rpm



DESCRIPTION

SOLBERG® RE-HEALING™ RF-MB foam concentrate from SOLBERG is an innovative environmentally sustainable fluorosurfactant and fluoropolymer-free multipurpose foam concentrate used to effectively extinguish Class A fuel fires and Class B hydrocarbon fuel fires including biofuels up to E-85. Proportioned at 0.5% for Class A fuels, and 3% solution for Class B fuels, SOLBERG RE-HEALING RF-MB foam can be used in fresh, sea or brackish water. SOLBERG RE-HEALING RF-MB foam possesses excellent burn back resistance due to its remarkable flow and rapid resealing characteristics. SOLBERG RE-HEALING foam concentrates are formulated using a new high performance synthetic foam technology to replace traditional AFFF, FFFP foam concentrates and older protein and fluoroprotein foams. RE-HEALING RF-MB foam concentrate contains no sediments.

STORAGE

The storage temperature range for SOLBERG RE-HEALING RF-MB foam concentrate is 1.7°C to 49°C (35°F to 120°F). The lowest temperature for use is -5°C (23°F).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

COMPATIBILITY

SOLBERG RE-HEALING RF-MB foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing, consult Perimeter Solutions Technical Services.

Materials of Construction Capability

SOLBERG RE-HEALING RF-MB foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about materials of construction compatibility, consult Perimeter Solutions Technical Services.

APPLICATION

SOLBERG RE-HEALING RF-MB foam concentrate is intended for use on Class A ordinary combustibles and Class B hydrocarbon fuel fires. It is not intended for use on Class B polar solvent fuels other than biofuels up to E-85. The foam can be used to prevent re-ignition of a liquid spill and control hazardous vapors. On Class A fuels, SOLBERG RE-HEALING RF - MB foam will improve extinguishment in deep-seated fires. Foam discharge devices such as air aspirating, as well as, non-air aspirating equipment can be used to obtain maximum results. The product may also be used as a pre-mix solution. SOLBERG RE-HEALING RF-MB foam is compatible with most dry powder (chemical) agents.

PERFORMANCE

Fire Performance

SOLBERG RE-HEALING RF-MB foam concentrate has been tested to and meets the fire performance test criteria of European Standard EN 1568 Part 3 (current edition).

Foam Proportioning

SOLBERG RE-HEALING RF-MB foam concentrate can be proportioned at the proper foam solution percentage using common foam proportioning devices such as:

- Eductors
- Inline balanced pressure proportioners
- Ratio controllers
- Self-educing nozzles

SOLBERG® RE-HEALING™ RF-MB FOAM CONCENTRATE

INSPECTION

SOLBERG RE-HEALING RF-MB foam concentrate or pre-mix solution should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

ENVIRONMENTAL INFORMATION

SOLBERG RE-HEALING foam concentrates do not contain intentionally added PFAS chemicals including PFOA and PFOS. In making this statement, SOLBERG relies on information provided by its raw material suppliers and certain independent laboratory analysis conducted on the product.

CERTIFICATIONS

SOLBERG manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters as well as the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

SOLBERG RE-HEALING RF-MB foam concentrate is Approved to European Standard EN 1568 Part 3 and meets the fire performance requirements of EN1568 Parts 1 and 4 as witnessed by DET NORSKE VERITAS (DNV) on E-85.

ORDERING INFORMATION

SOLBERG RE-HEALING RF-MB foam concentrate is available in pails, drums, totes and bulk quantities.

Part No.	Description	Approximate Shipping Weight	Approximate Cube
20180	SOLBERG RE-HEALING RF-MB, 20 litre (5 gallon) pail	21 kg (45 lb)	0.04 m ³ (1.25 ft ³)
20181	SOLBERG RE-HEALING RF-MB, 200 litre (55 gallon) drum	224 kg (495 lb)	0.33 m ³ (11.83 ft ³)
20182	SOLBERG RE-HEALING RF-MB, 1000 litre (265 gallon) tote	1118 kg (2465 lb)	1.42 m ³ (50.05 ft ³)
20183	SOLBERG RE-HEALING RF-MB, bulk	Call Customer Services	



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

10667 Jersey Blvd.
Rancho Cucamonga, CA 91730

Tel: +1 800 682 3626
Tel: +1 909 983 0772

salesfoamusa@perimeter-solutions.com

EMEA

Polígono de Baiña, Parcela 23
33682 Mieres (Asturias)

Spain
Tel: +34 985 24 29 45

salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia

Tel: +61 2 9673 5300

salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.