

# PHOS-CHEK® 1% AFFF FP

## AFFF FREEZE PROTECTED AQUEOUS FILM FORMING FOAM CONCENTRATE



### DESCRIPTION

**PHOS-CHEK® 1% AFFF FP** foam concentrate is proportioned at 1% concentration in both fresh and sea water and is effective on hydrocarbon fuels like gasoline, heptane, crude oil, and other fuels that are not soluble in water. Our 1% AFFF FP concentrate is ideal for use on fixed foam systems in space constrained low temperature -7 °F (-22 °C) areas and is compatible with standard proportioning and foam making devices. Because manual firefighting operations are labor intensive, PHOS-CHEK 1% AFFF FP concentrate is often the choice in emergency response requiring less time and space at the scene and optimizing the firefighters' time to fight the fire.

### APPLICATIONS

**PHOS-CHEK 1% AFFF FP** may be used with low expansion foam equipment (nozzles, monitors, foam chambers, etc.), non-aspirating devices (water spray nozzles and standard sprinklers) and medium expansion foam devices to fight fires involving Class B hydrocarbon fuel fires such as crude oil, aviation fuels, diesel, etc. It is not suitable for use on polar solvents or water miscible fuels such as alcohols, ketones, esters, and ethers.

### APPROVAL CERTIFICATIONS

UL 162 Listed and EN 1568-3:2008 (Class IB) Approved.

### SHELF LIFE, INSPECTION AND TESTING

The shelf life of any foam concentrate is maximized by proper storage conditions and maintenance. Factors affecting shelf life are wide temperature fluctuation, evaporation, dilution, and contamination by foreign materials. Properly stored PHOS-CHEK AFFF Class B foam concentrates should have no significant loss of firefighting performance for 20+ years. However, the National Fire Protection Association (NFPA) recommends annual testing of all firefighting foams.



### TYPICAL PHYSICAL PROPERTIES

<b>Specific Gravity @ 68 °F (20 °C)</b>	<b>1.020 – 1.060</b>
<b>pH</b>	<b>8.0 ± 0.5</b>
<b>Viscosity (LV-1 Spindle @ 60 RPM)*</b>	<b>8 – 18 cP</b>
<b>Refractive Index</b>	<b>1.4000 – 1.4100</b>
<b>Lowest Temperature for Use</b>	<b>0 °F (-18 °C)</b>
<b>Freezing Point</b>	<b>-7 °F (-22 °C)</b>

\*Brookfield LVT

### STORAGE AND HANDLING

The concentrate should be stored at temperatures between 35 °F (1.7 °C) and 120 °F (49 °C)\*\*; preferably in the original containers, approved bladder tanks, stainless steel, high density polyethylene, fiberglass or epoxy lined tanks. Concentrate piping acceptable materials of construction include stainless steel (either 304 or 316), some plastic piping including fiberglass and PVC, red brass, and black iron as long as the system is completely flooded eliminating the air/foam concentrate/carbon steel interface. Avoid permanent contact with carbon steel, iron, some copper alloys, & aluminum when the piping material and concentrate will be exposed to air. Galvanized piping should not be used in direct contact with the foam concentrate.

Foam concentrates are subject to evaporation, which accelerates when the product is exposed to air. Storage tanks should be sealed and fitted with a pressure vacuum vent to prevent free exchange of air.

\*\*EN APPROVAL: 35 °F (1.7 °C) and 122 °F (50 °C)

**HANDLING PRECAUTIONS**

- For DETAILED SAFETY INFORMATION, please refer to the SDS.
- **Precautionary Measures:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- **Eye Protection:** As a good industrial practice, the use of chemical goggles is recommended.
- **If in the eyes:** Flush with plenty of water.
- **Skin Protection:** Wear protective gloves when handling concentrate to minimize skin contact. Wash hands and contaminated skin after handling.
- **Respiratory Protection:** None required.
- For complete SDS, visit [perimeter-solutions.com](http://perimeter-solutions.com)

**PACKAGING**

ORDERING INFORMATION	Shipping Weight		Catalog #
1% AFFF FP	lb.*	kg.*	Part #
<b>5 Gallon Pail (20 litres)</b>	<b>43</b>	<b>19</b>	<b>10004058</b>
<b>55 Gallon Drum (200 litres)</b>	<b>468</b>	<b>212</b>	<b>10004057</b>
<b>265 Gallon Tote (1,000 litres)</b>	<b>2255</b>	<b>1023</b>	<b>10004056</b>

\*Approximate shipping weight

\*Contact your local authorized PHOS-CHEK distributor or factory sales representative for additional details. [perimeter-solutions.com](http://perimeter-solutions.com)



**FOR MORE INFORMATION**

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:  
[www.Perimeter-Solutions.com](http://www.Perimeter-Solutions.com)

**UNITED STATES**

1520 Brookfield Avenue  
Green Bay, WI 54313  
Tel: +1 800 682 3626  
Tel: +1 920 593 9445  
[salesfoamusa@perimeter-solutions.com](mailto:salesfoamusa@perimeter-solutions.com)

**EMEA**

Polígono de Baiña, Parcela 23  
33682 Mieres (Asturias)  
Spain  
Tel: +34 985 24 29 45  
[salesfoamea@perimeter-solutions.com](mailto:salesfoamea@perimeter-solutions.com)

**ASIA PACIFIC**

3 Charles Street  
St Marys NSW 2760 – Australia  
Tel: +61 2 9673 5300  
[salesfoamapac@perimeter-solutions.com](mailto:salesfoamapac@perimeter-solutions.com)

[perimeter-solutions.com](http://perimeter-solutions.com)

**NOTICE** PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.