

## EE-3

### NEWTONIAN TRAINING FOAM CONCENTRATE 3%



#### DESCRIPTION

Synthetic foam compound specially designed to be used for training and exhibition purposes, not for extinguishing. This product is formulated with synthetic surfactants easily biodegradable, with a low environmental impact. **It does not contain fluorochemicals.**

#### USE

Use with standard proportioning equipment and foam devices. EE-3 can be used to test, verify and exhibits foam equipment, for training fire brigades, etc, being the ideal product for training centers. It is an concentrate with extinguishing capability on class A and B (hydrocarbon) fires, but its burn-back resistance has been reduced voluntarily allowing the possibility to make successive tests in the same fire pool.



#### DOSAGE

The dosage rate is 3% in fresh or sea water for production of all types of foam.

#### SPECIFICATIONS

CONCENTRATE	
Specific gravity @ 20°C	1.02
pH @ 20°C	7.5
Viscosity, cone and plate, mPa.s @ 20°C	2.5
Freezing point, °C	-2°C

FOAM SOLUTION	
Dilution rate	3%
Surface tension at 20°C, mN/m (Demineralised water)	27
Interfacial tension with cyclohexane at 20°C, mN/m	3
Low Expansion Foam (EN 1568-3)	
Foam Expansion Index	10.0
25% Drainage Time, mins	3:30
Medium Expansion Foam (EN 1568-1)	
Foam Expansion Index	100
25% Drainage Time, mins	3:25

**PACKAGING**

The product is supplied in 20 or 25 L PE prismatic containers, 200 L PE cylindrical drums and 1,000 L IBC containers.

**STORAGE**

The foam concentrate shall be stored at temperatures between 0° and +50°C, preferably in their original containers, well sealed. The product has no expiration date.

**⚠ CAUTIONS**

Foams should not be used in contact with electrical equipments, nor with chemical products that can react with water. It is recommended to avoid the contact of the foam concentrate with the skin. In case of eye splashes, wash with plenty of water. In case of ingestion do not induce vomit, drink water and take medical advice.



**Solutions That Save.**

**FOR MORE INFORMATION**

Contact any of our worldwide  
Perimeter Solutions Fire Safety offices  
or visit:  
[www.Perimeter-Solutions.com](http://www.Perimeter-Solutions.com)

**UNITED STATES**

1520 Brookfield Avenue  
Green Bay, WI 54313  
Tel: +1 (920) 593-9445  
[salesfoamusa@perimeter-solutions.com](mailto:salesfoamusa@perimeter-solutions.com)

**EMEA**

Polígono Industrial de Baiña, Parcela 23  
33682 Baiña-Mieres (Asturias) – Spain  
Tel: +34 985 24 29 45  
[salesfoamea@perimeter-solutions.com](mailto:salesfoamea@perimeter-solutions.com)

**ASIA PACIFIC**

3 Charles Street  
St Marys NSW 2760 – Australia  
Tel: +61 2 9673 5300  
[salesfoamapac@perimeter-solutions.com](mailto:salesfoamapac@perimeter-solutions.com)

[perimeter-solutions.com](http://perimeter-solutions.com)

**NOTICE** PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.