

ARCTIC™ 3X3% ATC™ FOAM CONCENTRATE



TYPICAL PHYSICAL PROPERTIES

AT 77 °F (25 °C)

Appearance: Light yellow
non-newtonian liquid

Freezing Point: 28 °F (-2.2 °C)
(No quality loss after thawing)

Maximum Storage Temp: 120 °F (49 °C)

pH: 7.0 - 8.5

Refractive Index: 1.3545 - 1.3595

Specific Gravity: 1.000 - 1.040

Viscosity: 2400 - 3400 cP*

Sediments: <0.05%

*Brookfield Viscometer Spindle #4,
Speed 30 rpm



APPLICATION

ARCTIC 3x3 ATC foam concentrate can be applied to either Class B hydrocarbon or polar solvent^{††} fuel fires. The product is mixed 3 parts foam concentrate to 97 parts water. It may also be used as a 3% pre-mix solution. The foam can be used to prevent reignition of a liquid spill and control hazardous vapors. Foam discharge devices such as air aspirating, as well as, non-air aspirating equipment including standard fire sprinkler heads, can be used to obtain maximum results. SOLBERG ARCTIC 3x3 ATC foam is compatible with most powder (dry chemical) agents.[†]

PERFORMANCE

Fire Performance

ARCTIC 3x3 ATC foam concentrate has been tested to and meets the fire performance test criteria of Underwriters Laboratories, Inc. (UL) Listed – Standard 162 Underwriters' Laboratories of Canada (ULC) Standard S564 and FM Approval Standard 5130.

Foam Proportioning

ARCTIC 3x3 ATC foam concentrate can be proportioned at the proper foam solution percentage using most common proportioning devices^{††} such as:

- Eductors
- Inline balance pressure proportioners
- Ratio controllers
- Self-inducting nozzles

DESCRIPTION

ARCTIC™ 3x3 ATC™ foam concentrate from SOLBERG® is a synthetic, alcohol-resistant foam concentrate used to effectively extinguish Class B hydrocarbon and polar solvent fuel fires at 3% solution. ARCTIC 3x3 ATC foam concentrate provides rapid extinguishment and excellent burn back characteristics and can be used with fresh, salt and brackish water..

STORAGE

The storage temperature range for ARCTIC 3x3 ATC foam concentrate is 35 °F to 120 °F (1.7 °C to 49 °C).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

COMPATIBILITY

ARCTIC 3x3 ATC foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing of foam concentrates, consult Perimeter Solutions Technical Services.

Materials of Construction Capability

ARCTIC 3x3 ATC foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate.

INSPECTION

ARCTIC 3x3 ATC foam concentrate or pre-mix solutions should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25.

A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

ENVIRONMENTAL INFORMATION

ARCTIC 3x3 ATC foam concentrate is formulated with C6 fluorosurfactants and complies with the United States Environmental Protection Agency (USEPA) 2010 / 2015 PFOA Product Stewardship Program. ARCTIC foam concentrates do not contain PFOS.

CERTIFICATIONS

Solberg manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters and the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

[†]Not an FM Approved Configuration

^{††}See FM Approval Guide

ARCTIC™ 3X6% ATC™ FOAM CONCENTRATE

ARCTIC 3x3 ATC foam concentrate is Underwriters Laboratories, Inc. Listed in accordance with UL 162 (Standard for Safety for Foam Equipment and Liquid Concentrates), Underwriters' Laboratories of Canada Listed (Standard for Category 1 and 2 Foam Liquid Concentrates ULC S564) and FM Approved per

Approval Standard 5130.

ORDERING INFORMATION

ARCTIC 3x3 ATC foam concentrate is available in pails, drums, totes and bulk quantities.

ORDERING INFORMATION

Part No.	Description	Approximate Shipping Weight	Approximate Cube
20080	ARCTIC 3x3 ATC, 5 gallon (20 litre) pail	45 lb (21 kg)	1.25 ft ³ (0.04 m ³)
20081	ARCTIC 3x3 ATC, 55 gallon (200 litre) drum	495 lb (224 kg)	11.83 ft ³ (0.33 m ³)
20082	ARCTIC 3x3 ATC, 265 gallon (1000 litre) tote	2465 lb (1118 kg)	50.05 ft ³ (1.42 m ³)
20083	ARCTIC 3x3 ATC, bulk	Call Customer Services	



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue
Green Bay, WI 54313

Tel: +1 (920) 593-9445

salesfoamusa@perimeter-solutions.com

EMEA

Polígono Industrial de Baiña, Parcela 23
33682 Baiña-Mieres (Asturias) – Spain

Tel: +34 985 24 29 45

salesfoamea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia

Tel: +61 2 9673 5300

salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.